

Supported by:



0800 193 2523
info@fivemobility.co.uk
www.fivemobility.co.uk

Interlude 500

Bariatric Ultra-Low Bed



Technical specifications

Platform width: Adjustable from 89 cm to 97 cm to 104 cm to 119 cm to 134 cm

Overall width at 89cm: 101 cm

Overall width at 135cm: 144 cm

Platform length: 203 cm to 213 cm to 223 cm

Overall length at 203cm: 237 cm

Overall length at 224cm: 257 cm

Minimum height: 21 cm

Maximum height: 81 cm

Load capacity: 499 kg

Backrest angle: 70°

Footrest angle: 34°

Trendelenburg position: -14° to +14° (degrees)

Under bed clearance: 14.9 cm

Bed weight: 199 kg

Interlude 500

Features

- Easily expandable in width (press buttons) that can accommodate mattresses of 91cm, 99cm, 107cm, 122cm and even 137cm
- Load capacity of 499 kg for bariatric use
- Prevent Falls Related Injuries: 21 cm Ultra-Low Bed
- Ultra quiet DC motors. Helps maintain a calm and relaxed environment
- Emergency battery for temporary autonomy
- Easy to maintain with quick connect components
- Central brake: one pedal at the foot of the bed
- Lightweight composite head and footboard for ease of use.
- Antimicrobial and easy to clean powder coated steel structure
- 125mm anti-static double wheels casters
- 2 pairs of half-length composite siderails
- Patient remote control with auto-contour
- Patient control integrated into the bed siderails with auto-contour, underbed light and nurse call
- Nurse call built into the siderails with DB-37 connexion
- Easy to use nurse control integrated in the footboard
- Bed functions lock-out from the nurse control at the footboard
- Side and foot mattress retainer
- Backrest angle indicator
- Easily extendable in length without tools from 203 cm to 213 cm to 223 cm
- One-touch Trendelenburg adjustment
- Night light
- Multiple openings for restraint straps
- Bumpers at the head of the bed
- IV pole holders
- Trapeze bar receptacle
- Electric CPR
- Mechanical CPR: 2 handles

Accessories

- Bar with trapeze
- IV pole
- Left retractable IV pole
- Right retractable IV pole
- Support for oxygen cylinder
- Pump support
- DB-37 adapter cable
- Additional remote control
- Bed trolley
- Siderail protectors
- Mattress length extension 102 mm
- Mattress available with 3 width extension

Electronic

- Voltage: 120 V AC
- Amperage: 4 A
- Frequency: 60Hz
- Leakage current: <300 microamps
- Battery: 1.2aH sealed lead acid, 2 x 12V
- Scale accuracy (regardless of the bed position): 1% of the patient weight



Options

- Integrated scale with 2 zones bed exit notification, integrated warning signal to DB-37 port with visual and audible indicator

Supported by:



0800 193 2523

info@fivemobility.co.uk

www.fivemobility.co.uk